

T333 Series



Couplings and Plugs Kupplungen und Nippel	Connection Anschlüsse T	Order No Bestell Nr.	SW	Length Länge L	Dia. Durch- messer D
Female Thread Socket (inner Cone 60°) Kupplung mit Innengewinde 60° Con.	BSP 1/4" BSP 3/8" BSP 1/4" BSP 3/8"	T333 - 05 DG 13-60 T333 - 05 DG 17-60 T333 - 06 DG 13-60 T333 - 06 DG 17-60	17 19 17 19	66 66 66 66	20 20 20 20
Female Left Thread Socket (inner Cone 60°) Kupplung mit Innengewinde 60° Con. (Linken Seite)	BSP 1/4" Left BSP 3/8" Left BSP 1/4" Left BSP 3/8" Left	T333 - 05 LDG 13-60 T333 - 05 LDG 17-60 T333 - 06 LDG 13-60 T333 - 06 LDG 17-60	17 19 17 19	66 66 66 66	20 20 20 20
Hose Tail Socket Kupplung mit Schlauchtülle	Ø 7 Ø 10 Ø 7 Ø 10	T333 - 05 HG 07 T333 - 05 HG 10 T333 - 06 HG 07 T333 - 06 HG 10		46 46 46 46	20 20 20 20
Female Thread Plugs (inner Cone 60°) Nippel mit Innengewinde 60° Con.	BSP 1/4" BSP 3/8" BSP 1/4" BSP 3/8"	T333 - 05 DU 13-60 T333 - 05 DU 17-60 T333 - 06 DU 13-60 333 - 06 DU 17-60	17 19 17 19	50 50 50 50	19.5 22 19.5 22
Female Left Thread Plugs (inner Cone 60°) Nippel mit Innengewinde 60° Con (Linken Seite)	BSP 1/4" Left BSP 3/8" Left BSP 1/4" Left BSP 3/8" Left	T333 - 05 LDU 13-60 T333 - 05 LDU 17-60 T333 - 06 LDU 13-60 T333 - 06 LDU 17-60	17 19 17 19	50 50 50 50	19.5 22 19.5 22
Hose Tail Plugs Nippel mit Schlauchtülle	Ø 7 Ø 10	T333 - 05 HU 07 T333 - 05 HU 10		38 38	14 14

Interchangeability - Kompatibilität
IBEDA

Temperature Range-Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 20 bar (0 - 290 PSI)

Flow capacity - Größen
NW - 5 Oxygen - Sauerstoff
NW - 6 Fuel
Standard version - Standardversion
EPDM
Nickel plated - Vernickelt

Material - Material
Coupler Body-
Kupplungsgrundkörper : Brass Chrome Plated
Messing Verchromt

Back Part -
Rückwärtiger : Brass - Messing
Sleeve - Hülse : Brass Chrome Plated
Messing Verchromt

Valve - Ventil : Brass - Messing
Springs - Federn : Stainless Steel -
Edelstahl

Locking O-Ring-
Sprengling : Stainless Steel -
Edelstahl
Balls - Kugeln : AISI 420 Hardened -
AISI 420 Gehärtet

Seals - Dichtungen : EPDM
Plug - Nippel : Brass Chrome Plated
Messing Verchromt

Using Area
The 333 serie couplers are used
for pressure regulators, fuel, gas,
oxygen and cutting as well as welding
torches allied processes.

Anwendung
The 333 Serie-Kupplungen ist für
Druckregulatoren, Fuel-Oil-, Gas- und
Schweißprozessen geeignet.

