



SUPER FLOW LINE SUPERFLUSSLINE



2500 l/min



Interchangeability - Kompatibilität
ATLAS COPCO QIC 15, RECTUS 34

Temperature Range-Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Größen
NW - 10



Standard version - Standardversion
Nitrile (Ni) - NBR (Ni)
Nickel plated - Vernickelt

Options - Optionen
F - Straight through flow -
ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung

**For optional orders please add the symbol
of your option end of the order no.
Für optionale Bestellungen das
Kennbuchstabe und Bestell-Nr bitte
hinzufügen** (Beispiel: T034 EG 13-K-V)

Material - Material

Coupler Body- Kupplungsgrundkörper	: Steel Nickel Plated - Stahl vernickelt
Back Part - Rückwärtiger	: Brass Nickel Plated - Messing vernickelt
Sleeve - Hülse	: Steel Nickel Plated - Stahl vernickelt
Valve - Ventil	: Zinc Diecasting -
Springs - Federn	: Stainless Steel - Edelstahl
Locking O-Ring- Sprengling	: Stainless Steel - Edelstahl
Balls - Kugeln	: Stainless Steel - Edelstahl AISI 420
Seals - Dichtungen	: Nitrile (Ni) - NBR (Ni)
Plug - Nippel	: Steel Nickel Plated - Stahl vernickelt

Couplings and Plugs Kupplungen und Nippel	Connection Anschlüsse	Order No Bestell Nr.	SW	Length Länge	Dia. Durch- messer
 Male Thread Couplings Kupplungen mit Außengewinde	R 1/4"	T034 RG 13	24	70	28
	R 3/8"	T034 RG 17	24	70	28
	R 1/2"	T034 RG 21	24	72	28
	R 3/4"	T034 RG 26	27	72	28
 Female Thread Couplings Kupplungen mit Innengewinde	G 1/4"	T034 DG 13	24	65	28
	G 3/8"	T034 DG 17	24	65	28
	G 1/2"	T034 DG 21	24	65	28
	G 3/4"	T034 DG 26	30	66	28
 Standard Hose Barb Couplings Kupplungen mit Schlauchanschluß	6 mm - 1/4"	T034 HG 06	24	83	28
	8 mm - 5/16"	T034 HG 08	24	83	28
	10 mm - 3/8"	T034 HG 10	24	83	28
	13 mm - 1/2"	T034 HG 13	24	83	28
	16 mm - 5/8"	T034 HG 16	24	83	28
	19 mm - 3/4"	T034 HG 19	24	83	28
 Standard Hose Barb Plugs Nippel mit Schlauchanschluß	6 mm - 1/4"	T034 HU 06		53	
	10 mm - 3/8"	T034 HU 10		53	
	13 mm - 1/2"	T034 HU 13		53	
	16 mm - 5/8"	T034 HU 16		53	
 Male Thread Plugs Nippel mit Außengewinde	R 3/8"	T034 RU 17	19	48	
	R 1/2"	T034 RU 21	22	52	
 Female Thread Plugs Nippel mit Innengewinde	G 3/8"	T034 DU 17	19	40	
	G 1/2"	T034 DU 21	24	40	

