



SUPER FLOW LINE SUPERFLUSSLINE



1800 l/min



Interchangeability - Kompatibilität
RECTUS 38,,HANSEN 6000

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508PSI)

Flow capacity - Größen
NW - 15









Standard version - Standardversion
Nitrile (Ni) - NBR (Ni)

Options - Optionen
F - Straight through flow -
ungehinderter Durchfluss
K - Chrome plated - Verchromt
N - Nickel plated - Vernickelt
S - Stainless Steel - Edelstahl
(S3:AISI 303, S6:AISI 316TI)
V - Viton Seal - Viton Dichtung

**For optional orders please add the symbol
of your option end of the order no.
Für optionale Bestellungen das
Kennbuchstabe und Bestell-Nr bitte.
hinzufügen (Beispiel: T027 EG 13-K-V)**

Material - Material

Coupler Body -
Kupplungsgrundkörper : Brass Nickel Plated -
Messing vernickelt
Sleeve - Hülse : Steel Nickel Plated -
Stahl vernickelt
Valve - Ventil : Brass - Messing
Springs - Federn : Stainless Steel -
Edelstahl
Locking O-Ring-
Sprengring : Stainless Steel -
Edelstahl
Balls - Kugeln : Stainless Steel -
Edelstahl AISI 420
Seals - Dichtungen : Nitrile NBR - NBR
Plug - Nippel : Steel Nickel Plated -
Stahl vernickelt

Couplings and Plugs Kupplungen und Nippel	Connection Anschlüsse	Order No Bestell Nr.	SW	Length Länge	Dia. Durch- messer
 Male Thread Couplings Kupplungen mit Außengewinde	R 1/4"	T027 EG 13	24	63	28
	R 3/8"	T027 EG 17	24	63	28
	R 1/2"	T027 EG 21	24	65	28
	R 3/4"	T027 EG 26	27	65	28
	NPT 3/8"	T027 TG 17	24	63	28
	NPT 1/2"	T027 TG 21	24	65	28
 Female Thread Couplings Kupplungen mit Innengewinde	NPT 3/4"	T027 TG 26	27	65	28
	G 1/4"	T027 DG 13	24	57	28
	G 3/8"	T027 DG 17	24	57	28
	G 1/2"	T027 DG 21	24	57	28
 Standard Hose Barb Couplings Kupplungen mit Schlauchanschluß	G 3/4"	T027 DG 26	30	58	28
	NPT 3/8"	T027 NG 17	24	57	28
	NPT 1/2"	T027 NG 21	24	57	28
	NPT 3/4"	T027 NG 26	30	58	28
	6 mm - 1/4"	T027 HG 06	24	75	28
	8 mm - 5/16"	T027 HG 08	24	75	28
 Standard Hose Barb Plugs Nippel mit Schlauchanschluß	9 mm - 5/14"	T027 HG 09	24	75	28
	10 mm - 3/8"	T027 HG 10	24	75	28
	13 mm - 1/2"	T027 HG 13	24	75	28
	16 mm - 5/8"	T027 HG 16	24	75	28
	19 mm - 3/4"	T027 HG 19	24	75	28
	6 mm - 1/4"	T027 HU 06		48	
 Male Thread Plugs Nippel mit Außengewinde	8 mm - 5/16"	T027 HU 08		48	
	9 mm - 5/14"	T027 HU 09		48	
	10 mm - 3/8"	T027 HU 10		48	
	13 mm - 1/2"	T027 HU 13		48	
	16 mm - 5/8"	T027 HU 16		48	
	19 mm - 3/4"	T027 HU 19		48	
 Female Thread Plugs Nippel mit Innengewinde	R 1/4"	T027 RU 13	17	43	
	R 3/8"	T027 RU 17	17	43	
	R 1/2"	T027 RU 21	22	48	
	R 3/4"	T027 RU 26	27	50	
	NPT 3/8"	T027 TU 17	17	43	
	NPT 1/2"	T027 TU 21	22	48	
 Female Thread Plugs Nippel mit Innengewinde	NPT 3/4"	T027 TU 26	27	50	
	G 1/4"	T027 DU 13	17	40	
	G 3/8"	T027 DU 17	19	40	
	G 1/2"	T027 DU 21	24	46	
	G 3/4"	T027 DU 26	30	46	
	NPT 3/8"	T027 NU 17	19	40	
 Female Thread Plugs Nippel mit Innengewinde	NPT 1/2"	T027 NU 21	24	46	
	NPT 3/4"	T027 NU 26	30	46	

