








T205-K Series



Couplings and Plugs Kupplungen und Nippel	Connection Anschlüsse	Order No Bestell Nr. ▲	Order No Bestell Nr. ■	SW	Length Länge	ØD
 Male Threaded Coupler To ISO-228 Kupplung mit Aussengewinde zu ISO-228	BSP 1/4"	T205K EGB 313	T205 EGB 413	19	58	25
	BSP 3/8"	T205K EGB 317	T205 EGB 417	19	59	25
	BSP 1/2"	T205K EGB 321	T205 EGB 421	22	62	25
 Female Threaded Coupler To ISO-228 Kupplung mit Innengewinde zu ISO-228	BSP 1/4"	T205K DGB 313	T205 DGB 413	19	57	25
	BSP 3/8"	T205K DGB 317	T205 DGB 417	22	58	25
 Right Side Female Connection Gewinde Auf der Rechten Seite	BSP 1/4"(R)	T205K CGB 313	T205 CGB 413	19	61	25
	BSP 3/8"(R)	T205K CGB 317	T205 CGB 417	22	63	25
 Left Side Female Connection Gewinde Auf der Linken Seite	BSP 1/4"(L)	T205K LGB 313	T205 LGB 413	19	61	25
	BSP 3/8"(L)	T205K LGB 317	T205 LGB 417	22	63	25
 Hose Tail Coupler Kupplung mit Schlauchanschluß	Ø 6	T205K HGB 306	T205 HGB 406	19	70	25
	Ø 9	T205K HGB 309	T205 HGB 409	19	75	25
	Ø 11	T205K HGB 311	T205 HGB 411	19	75	25
	Ø 13	T205K HGB 313	T205 HGB 413	19	75	25
 Hose Tail Coupler Kupplung mit Schlauchanschluß	Ø 7	T205K HGB 307	T205 HGB 407	19	77	25

Interchangeability - Kompatibilität
WALTHER UF - 006

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 40 bar (0 - 580 PSI)

Flow capacity - Größen
NW - 6 (30 mm²)


Option - Optionen (Material - Material)
S - Stainless Steel - Edelstahl
C - Steel - Stahl

**For optional orders please add the symbol
of your option end of the order no.
Für optionale Bestellungen das
Kennbuchstabe und Bestell-Nr bitte.
hinzufügen (Beispiel: T205 EGB 313 - K - V)**










Material - Material

Coupler body - Kupplungsgrundkörper	:Brass Passivated - Messing Passiviert
Back Part - Rückwärtiger	:Brass Passivated - Messing Passiviert
Sleeve - Hülse	:Brass Passivated - Messing Passiviert
Valve - Ventil	:Brass Passivated - Messing Passiviert
Springs - Federn	:Stainless Steel - Edelstahl
Balls - Kugeln	:AISI 420 & Hardened - Gehärtet AISI 420
Seals - Dichtungen	:Nitrile seal NBR (Ni) - Nitrilgummi
Plug - Nippel	:Brass Passivated - Messing Passiviert

Self Sealing Plugs Verschlußnippel

 Male Threaded Shut-Off Plug To ISO-228 Nippel mit Aussengewinde zu ISO-228 absperrend	BSP 1/4"	T205K EUB 313	T205K EUB 413	19	56	25
	BSP 3/8"	T205K EUB 317	T205K EUB 417	19	57	25
	BSP 1/2"	T205K EUB 321	T205K EUB 421	22	60	25



Couplings and Plugs Kupplungen und Nippel	Connection Anschlüsse	Order No Bestell Nr. ▲	Order No Bestell Nr. ■	SW	Length Länge	ØD
 Dişi Dişli Valfli Uç ISO-228 Female Threaded Shut-Off Plug To ISO-228	BSP 1/4"	T205K DUB 313	T205K DUB 413	19	55	25
	BSP 3/8"	T205K DUB 317	T205K DUB 417	22	56	25
 Sağ Dişli Dişi Bağlantı Right Side Female Connection	BSP 1/4"(R)	T205K CUB 313	T205K CUB 413	19	59	25
	BSP 3/8"(R)	T205K CUB 317	T205K CUB 417	22	61	25
 Sol Dişli Dişi Bağlantı Left Side Female Connection	BSP 1/4"(L)	T205K LUB 313	T205K LUB 413	19	59	25
	BSP 3/8"(L)	T205K LUB 317	T205K LUB 417	22	61	25
 Valfli Hortum Uç Hose Tail Shut-Off Plug	Ø 6	T205K HUB 306	T205K HUB 406	19	70	25
	Ø 9	T205K HUB 309	T205K HUB 409	19	75	25
	Ø 11	T205K HUB 311	T205K HUB 411	19	75	25
	Ø 13	T205K HUB 313	T205K HUB 413	19	75	25
 Valfli Hortum Uç Hose Tail Shut-Off Plug	Ø 7	T205K HUB 307	T205K HUB 407	19	70	25
Thru Flow Plugs						
 Valfli Erkek Dişli Uç ISO-228 Male Threaded Plug To ISO-228	BSP 1/4"	T205K EU 313	T205K EU 413	17	37	19
	BSP 3/8"	T205K EU 317	T205K EU 417	19	38	21
	BSP 1/2"	T205K EU 321	T205K EU 421	22	41	24
 Dişi Dişli Uç Female Threaded Plug	BSP 1/4"	T205K DU 313	T205K DU 413	19	37	19
	BSP 3/8"	T205K DU 317	T205K DU 417	22	41	19
 Hortum Uç Hose Tail Plug	Ø 6	T205K HU 306	T205K HU 406		48	16
	Ø 9	T205K HU 309	T205K HU 409		53	16
	Ø 11	T205K HU 311	T205K HU 411		53	16
	Ø 13	T205K HU 313	T205K HU 413		53	16
 Hortum Uç Hose Tail Plug	Ø 7	T205K HU 307	T205K HU 407		48	16

Interchangeability - Kompatibilität
WALTHER UF - 006

Temperature Range -
Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 50 bar (0 - 580 PSI)

Flow capacity - Größen
NW - 6 (30 mm Sq)

Option - Optionen (Material - Material)
S - Stainless Steel - Edelstahl
C - Steel - Stahl

**For optional orders please add the symbol
of your option end of the order no.
Für optionale Bestellungen das
Kennbuchstabe und Bestell-Nr bitte.
hinzufügen (T205-K EGB 313 K-V)**

Material - Material

Coupler body - Kupplungsgrundkörper	:Brass Passivated - Messing Passiviert
Back Part - Rückwärtiger	:Brass Passivated - Messing Passiviert
Sleeve - Hülse	:Brass Passivated - Messing Passiviert
Valve - Ventil	:Brass Passivated - Messing Passiviert
Springs - Federn	:Stainless Steel - Edelstahl
Balls - Kugeln	:AISI 420 & Hardened - Gehärtet AISI 420
Seals - Dichtungen	:Nitrile seal NBR (Ni) - Nitrilgummi
Plug - Nippel	Dichtung NBR (Ni) :Brass Passivated - Messing Passiviert

